



Dimensions	215mm x 361mm x 315mm (h)	8.46in x 14.21in x 12.4in (h)	
Weight	12,2 kg	26,9 lb	
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz
Current Consumption	1,7A	1,9A	
Compressor Power	1/8 HP		
Power Consumption (Cooling)	150 W	510 Btu/h	
Power Consumption (Heating)	\		
Cooling Capacity *	250 W	850 Btu/h	
Minimum Water Flow	400 l/h	105 Usgal/h	
Air Flow	\		
Maximum Exchanger's Pressure	0,5 bar	7,3 PSI	
Ambient Temperature Range	5°C - 38°C	32°F - 100°F	
Certification \ Protection Grade	CE \ IPX4		
Gas Type and Quantity	R134a \ 110 g		
* the value reported refers to the following condition: room temperature 30°C (86°F), water temperature 25°C (77°F)			

Material:	Drawing: TK 150 – technical data		
Thickness:	File: TK_150_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1: 5	Date: 31/10/2014
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Matteo		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ARCHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Modify:

Drawer: